interstuhl

Technical data sheet 560E

Specification Cantilever frame, black, stackable

Backrest:	H:	435
Seat:	H:	445
	W:	465
	D:	415
Total:	H:	890
	W (ArmR):	555
	D:	560
Weight: Volume:	kg m³	10,5 0,39
	Seat: Total: Weight:	Seat: H: W: D: Total: H: W (ArmR): D: Weight: kg



Basic equipment		Benefit
Plastic parts	Colour maintained throughout, black.	Colourfast and resistant to deep scratches and abrasions.
Jpholstery	Seat upholstery: 30 mm foam.	Great seating comfort.
Frame	Tubular steel Ø 20 x 2,5 mm, powder coated, as colour finish (plastic parts).	
Seat carrier	Plastic	
Stackability	4 chairs.	
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Standards	EN 68878 for visitor chairs. GS-Symbol for tested safety and tested for contaminants.	Hight safety and great comfort.
Certification	Quality management system DIN EN ISO 9001:2000, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2005. Quality Office, Blue Angel, Golden M.	High quality product.
Narranty and return	5 years long term and 3 years full warranty. Complete return and recycling guarantee.	Exchange of parts free of charge within the guaranteed periods.

interstuhl

Technical data sheet 560E

Specification Cantilever frame, black, stackable

Dimensions in mm	Backrest:	H:	435
Dimensions in min	Backrest:	H:	435
	Seat:	H:	445
		W:	465
		D:	415
	Total:	H:	890
		W (ArmR):	555
		D:	560
Packaging data	Weight:	kg	10,5
	Volume:	m³	0,39



Options		Benefit
Frame	Powder coated brilliant silver or cromed.	Individual design.
Glides	Felt glides for hard floors.	Ideal stability and protection of the floor.
Materials (fabric)	Various fabric and leather options available.	Individual design.