interstuhl

Technical data sheet 27V4

Specification Swivel chair medium height, management upholstery

| Dimensions in mm | Backrest: | H: | 520 |
|------------------|-----------|--------------|-----------|
| | Seat: | H: | 420 - 540 |
| | | W: | 500 |
| | | D: | 520 |
| | Total: | H: | 1140 |
| | | W (no ArmR): | 545 |
| | | W (ArmR): | 600 |
| | | D: | 610 |
| Packaging data | Weight: | kg | 19,5 |
| | Volume: | m³ | 0,65 |
| | | | |



Benefit

Basic equipment

| Backrest | Back medium high, upholstered 30 mm foam. Integrated headrest. | Great seating comfort due to the ergonomically designed backrest. |
|------------------------|---|---|
| Jpholstery | Comfort seat upholstered. Breath actively moulding foam, CFC - CHC - free (segregated foam). Seat 35 mm foam + 10 mm cotton. | Paddings are unglued, ensuring optimal air movement, breathable. |
| Mechanism | Smart Motion Technology, lockable in 4 positions. Opening angle between seat and back up to 110°. | The perfectly kinematic movement of the Smart Motion Technology encourages the user to change seating position frequently; in addition, the active seat inclination supports an ergonomic position especially when working at the desk. |
| Seat height adjustment | Seat height adjustment infinitely variable from 420 - 540 mm. Self-supporting safety gas spring. | Even people outside the DIN range (i.e. taller than 192 cm and smaller than 151cm) will sit in the most ergonomic way. |
| Seat depth adjustment | Sliding seat for individual seat depth adjustment. Can be adjusted by 70 mm. | The real support area for the thighs of taller people will be enlarged. |
| seat inclination | Flexible adaption to users movements forward +2° and backward -5°, lockable | The inclination prevents the pelvis from tilting to the reat, ensures the right position of the spinal column. |
| /eight Adjustment | From 45 - 130kg, adjustable per ratchet element in 10 levels. | Individual adjustment of the backrest and the back pressure to the weight and height of the user. |
| astors | Hard castors, load-dependent braked, for soft floors (according to DIN EN 12529). | The chair does not roll away in an off-loaded situation, minimum risk of accident. |
| ase | Aluminium base, polished. | Very high stability, long service life. |
| Materials | All materials are segregated and recyclable. | Environmentally friendly. |
| Standards | EN 1335 for office swivel chairs and office swivel armchairs. GS-symbol for having tested safety, tested for contaminants and ergonomics. | High quality product and great comfort. |
| | | |

interstuhl

Technical data sheet 27V4

Specification Swivel chair medium height, management upholstery

| Dimensions in mm | Backrest: | H: | 520 | |
|---------------------|-----------|---|--|--|
| | Seat: | H: | 420 - 540 | The same start party same same same same same same same same |
| | | W: | 500 | |
| | | D: | 520 | |
| | Total: | H: | 1140 | |
| | | W (no ArmR): | 545 | |
| | | W (ArmR): | 600 | |
| | | D: | 610 | |
| Packaging data | Weight: | kg | 19,5 | |
| | Volume: | m³ | 0,65 | |
| Certification | | 9001:2015, Reg (EMAS), Enviror DIN EN ISO 140 Management Sy EcoVadis Gold. Commitment to s | ement system DIN EN ISO ulation (EC) no. 1221/2009 mental Management System 01:2015, Health and Safety rstem DIN EN ISO 45001:2018, Commitment to sustainability, sustainability. Quality Office, na e3 level Platin. | High quality product. |
| Warranty and return | | 10 years warran recycling guaran | ty. Complete return and itee. | Exchange of parts free of charge within the guaranteed period. |

Disassembly instructions are available upon request for any interstuhl product

interstuhl

Technical data sheet 27V4

Options

Specification Swivel chair medium height, management upholstery

| Dimensions in mm | Backrest: | H: | 520 |
|------------------|-----------|--------------|-----------|
| | Seat: | H: | 420 - 540 |
| | | W: | 500 |
| | | D: | 520 |
| | Total: | H: | 1140 |
| | | W (no ArmR): | 545 |
| | | W (ArmR): | 600 |
| | | D: | 610 |
| Packaging data | Weight: | kg | 19,5 |
| | Volume: | m³ | 0,65 |
| | | | |



Benefit

| - | | |
|--------------------------|---|---|
| Castors | Soft castors, load-dependent braked, for hard floors (acc. to DIN EN 12529) or glides (soft/hard). | The chair does not roll away in an off-loaded situation, minimum risk of accident. |
| Base | Aluminium base, chromed. | Very high stability, longevity. |
| Mechanical sprung column | Also in the lowest seating position. | Damping of an excessive vertical impact, so that the spine will be preserved. |
| Lumbar support | Depth- (26 mm) and height adjustable (64 mm). | The lumbar support is depth adjustable and can be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible. |
| Armrests | Aluminium ring arm rests with or witouth leather pads, polished or chromed. 3D Auto Flow arm rests, adj. in height (100 mm) & width (460 - 530 mm), soft. 3D T-arm rests, adj. in height (100 mm) & width (450 - 520 mm), depth (60 mm), soft. | The armrests relieve the neck and shoulder muscles. |
| Material | Several fabric collections are available in different colours. | During the design of the chair several colours and upholstery materials are available. |
| Accessories | Coat hanger, polypropylene black. | |

Disassembly instructions are available upon request for any interstuhl product