# interstuhl

#### Technical data sheet 32V4

Specification Swivel armchair high,seat&backr.,fabric Manag.Uph.

Dimensions in mm	Backrest:	H:	770
	Seat:	H:	420-540
		W:	500
		D:	520
	Total:	H:	1400
		W (no ArmR):	545
		W (ArmR):	600
		D:	650
Packaging data	Weight:	kg	21
	Volume:	m³	0,65



Basic equipment		Benefit
Backrest	Back high, upholstered 30 mm foam. Integrated headrest.	Great seating comfort due to the ergonomically designed backrest.
Upholstery	Comfort seat upholstered. Breath actively moulding foam, CFC - CHC - free ( segregated foam). Seat 35 mm foam + 10 mm cotton.	Paddings are unglued, ensuring optimal air movement, breathable.
Mechanism	Smart Motion Technology, lockable in 4 positions. Opening angle between seat and back up to 110°.	The perfectly kinematic movement of the Smart Motion Technology encourages the user to change seating position frequently; in addition, the active seat inclination supports an ergonomic position especially when working at the desk.
Seat height adjustment	Seat height adjustment infinitely variable from 420 - 540 mm. Self-supporting safety gas spring.	Even people outside the DIN range (i.e. taller than 192 cm and smaller than 151cm) will sit in the most ergonomic way.
Seat depth adjustment	Sliding seat for individual seat depth adjustment. Can be adjusted by 70 mm.	The real support area for the thighs of taller people will be enlarged.
Seat inclination	Flexible adaption to users movements forward +2° and backward -5°, lockable	The inclination prevents the pelvis from tilting to the reat, ensures the right position of the spinal column.
Weight Adjustment	From 45 - 130kg, adjustable per ratchet element in 10 levels.	Individual adjustment of the backrest and the back pressure to the weight and height of the user.
Castors	Hard castors, load-dependent braked, for soft floors (according to DIN EN 12529).	The chair does not roll away in an off-loaded situation, minimum risk of accident.
Base	Aluminium base, black.	Very high stability, long service life.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Standards	EN 1335 for office swivel chairs and office swivel armchairs. GS-symbol for having tested safety, tested for contaminants and ergonomics.	High quality product and great comfort.

# interstuhl

### Technical data sheet 32V4

Specification Swivel armchair high,seat&backr.,fabric Manag.Uph.

Dimensions in mm	Backrest:	H:	770
	Seat:	H:	420-540
		W:	500
		D:	520
	Total:		
		H:	1400
		W (no ArmR):	545
		W (ArmR):	600
		D:	650
Packaging data	Weight:	kg	21
Fackaging data	0	-	
	Volume:	m³	0,65



Certification	Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Health and Safety Management System DIN EN ISO 45001:2018, EcoVadis Gold. Commitment to sustainability. Quality Office, Blue Angel, Bifma e3 level Platin.	High quality product.
Warranty and return	10 years warranty. Complete return and recycling guarantee.	Exchange of parts free of charge within the guaranteed period.

Disassembly instructions are available upon request for any interstuhl product

### interstuhl

#### Technical data sheet 32V4

Specification Swivel armchair high, seat&backr., fabric Manag.Uph.

Dimensions in mm	Backrest:	H:	770
	Seat:	H:	420-540
		W:	500
		D:	520
	Total:	H:	1400
		W (no ArmR):	545
		W (ArmR):	600
		D:	650
Packaging data	Weight:	kg	21
	Volume:	m³	0,65



Options		Benefit
Castors	Soft castors, load-dependent braked, for hard floors (acc. to DIN EN 12529) or glides (soft/hard).	The chair does not roll away in an off-loaded situation, minimum risk of accident.
Base	Aluminium base, anthracite, chromed or aluminium polished.	Very high stability, longevity.
Mechanical sprung column	Also in the lowest seating position.	Damping of an excessive vertical impact, so that the spine will be preserved.
umbar support	Depth- (26 mm) and height adjustable (64 mm).	The lumbar support is depth adjustable and can be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible.
Armrests	Aluminium ring arm rests with or witouth leather pads, polished or chromed. 3D Auto Flow arm rests, adj. in height (100 mm) & width (460 - 530 mm), soft. 3D T-arm rests, adj. in height (100 mm) & width (450 - 520 mm), depth (60 mm), soft.	The armrests relieve the neck and shoulder muscles.
Material	Several fabric collections are available in different colours.	During the design of the chair several colours and upholstery materials are available.
Accessories	Coat hanger, polypropylene black.	

Disassembly instructions are available upon request for any interstuhl product