

**Technical data sheet 10V2**

Specification Swivel chair, low

Dimensions in mm	Backrest:	H:	500-550
		Seat:	H: 410-525 W: 485 D: 480
	Total:	H:	1075
		W (no ArmR):	700
		W (ArmR):	700
		D:	700
	Packaging data	Weight:	kg
Volume:		m³	0,69



**Basic equipment**

**Benefit**

Backrest	Backrest low incl. backrest height adjustment through snap lock mechanism by 50 mm. Backrest upholstery: 30 mm foam. Inlay, colour/surface the same as the base.	The back mainly has to be supported in the area of the 4th and 5th lumbar vertebra. (corresponding to EN 1335) In this way a relaxed and comfortable sitting is possible. Backrest height adjustment easy to be adjusted when sitting.
Upholstery	Seat and back upholstery. Breathable moulded foam, CFC and CHC-free (pure foam). Seat: 70 mm + 10 mm cotton.	Optimum microclimate through unglued upholstery, breathable.
Mechanism	Body-Float synchro mechanism with a max. opening angle of 125°.	The Body-Float synchro mechanism from Interstuhl is designed to offer the body optimum support in any seated position and at the same time facilitate the change between various postures.
Seat height adjustment	Infinitely variable from 410 - 525 mm. Self-supporting safety pneumatic spring.	The correct seat height is the basic condition for right ergonomic and relaxed sitting and working.
Bounce spring	Additional mechanical bounce spring also in lowest position.	The bounce spring cushions the impact on sitting down, thus gentle on the spine.
Weight adjustment	Infinitely adjustable to a body weight of 50 - 120 kg.	Individual adjustment of backrest support weight and height of the seated person.
Castors Ø 65 mm	Hard double castors, load-dependent braked, for soft floors. (corresponding to DIN EN 12529)	The chair does not roll away when not in use, minimises the risk of accidents.
Base	Aluminium-base powder-coated, black,	High stability, long service life.
Materials	All materials are pure and recyclable.	Environmentally friendly.
Standards	EN 1335 for office swivel chairs and office swivel executive chair GS-Symbol for tested safety. Ergonomics and pollutant tested.	High safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2000, EMAS acc. to EC Directive 1221/2009, Environmental management system DIN EN ISO 14001:2005. Quality Office, Golden M, Blue Angel.	High-quality product.
Warranty and return	5 year long-term and 3 year full warranty. Full return and recycling warranty.	High safety and long service life by minimising costs. Free parts replacement within the warranty period.

**Technical data sheet 10V2**

Specification Swivel chair, low

Dimensions in mm	Backrest:	H:	500-550	
		Seat:	H:	410-525
			W:	485
	Total:	D:	480	
		H:	1075	
		W (no ArmR):	700	
		W (ArmR):	700	
Packaging data	D:	700		
	Weight:	kg	26,5	
	Volume:	m <sup>3</sup>	0,69	



**Technical data sheet 10V2**

Specification Swivel chair, low

Dimensions in mm	Backrest:	H:	500-550	
		Seat:	H:	410-525
			W:	485
	Total:	D:	480	
		H:	1075	
		W (no ArmR):	700	
Packaging data	Weight:	kg	26,5	
		Volume:	m³	0,69
		W (ArmR):	700	
		D:	700	



<b>Options</b>		<b>Benefit</b>
Castors Ø 65 mm / Glides	Soft castors, load-dependent braked, for hard floors or felt glides. (corresponding to DIN EN 12529)	The chair does not roll away when not in use, minimises the risk of accidents.
Base	Aluminium base, brushed.	Very high stability, long service life.
Armrests	T-armrests height adjustable (5 steps, 75 mm), black ring armrest, black with panel (the same colour as the base).	The adjustable height of the armrests also takes the strain off the neck muscles.
Fabric materials	Several fabric qualities and leather in various colours are available.	A wealth of possibilities to design the chair.